

GJD101


Detector PIR de exterior cu element dual MX-35




Specificatii tehnice

- Element detectie: PIR dual MX-35
- Raza detectie: 10 ÷ 35 m ajustabil
- Unghi acoperire: 90°
- Reglaj impuls: 4 trepte
- Alimentare 9-15 Vcc
- Consum stand-by: 9 mA
- Consum alarma: 50 mA
- Microprocesor ASIC Digital
- Posibilitate de mascare a ariei de detectie pentru aplicatii Pet immunity
- Ajustare: 180° pan / 90° tilt
- Lentila Fresnel cu 36 zone si filtru de lumina alba
- Temperatura: -20° C+55° C
- Carcasa: ABS
- Culoare: alba
- Grad protectie: IP 55
- Capac frontal cu protectie UV
- Inaltime instalare: variabila 1.6÷6m (optima 3m)

Acoperire



Disponerea fasciolelor pentru distanta maxima de acoperire.



Disponerea fasciolelor pentru distanta minima de acoperire.


Mascand partea superioara a lentilei raza de detectie se reduce la 20m

Mascand partea superioara a lentilei raza de detectie se reduce la 6m

Aplicatii tipice


Volumetric 1

Inaltime montaj: 3 m
Distanța detectie: 35 m




Volumetric 2

Inaltime montaj: 6 m
Distanța detectie: 35 m




Pet immunity

Inaltime montaj: 1.5 m
Distanța detectie: 35 m



Perdea

Inaltime montaj: 6 m
Distanța detectie: 35m



Dimensiuni

