

PATROL 401 PET


Caracteristici

PATROL- 401PET este imun la animale pana la 35kg si inaltime de 1 metri.


- PATROL- 401PET**, echipat cu senzor QUAD, formeaza mai multe segmente de zone de detectie care permite o focusare mai precisa a razelor IR din aria de detectie.




QUAD ELEMENT PYROELECTRIC INFRARED SENSOR



BIPOLAR PULSE COUNTER



WIDE ANGLE LENS



Specificatii tehnice

Viteza detectie:	0.3 - 3.0m/sec;
Alimentare:	8.5 - 16VDC;
Consum:	
Veghe:	12.7mA;
In alarma cu LED aprins:	9.7mA;
In alarma cu LED stins:	6.8mA;
Implulsuri bipolare:	1,2;
Perioada alarma:	3sec;
Distanta acoperire:	15 metri;
Iesire releu:	60V; 120mA; 16Ω;
Perioada warm up:	40sec;
Timp resetare:	5±1sec;
Imunitate la lumina alba:	nu mai putin de 10000Lux;
Protectie antisabotaj:	Microinterrupator deschidere;
Temperatura de functionare	-30°C +50°C;
Temperatura de stocare:	-40°C +80°C;
Imunitate RFI:	30V/m in gama de frecvente 10MHz – 1000MHz
Imunitate EMI:	50000V;
Dimensiuni:	93mm x 66mm x 46mm;
Greutate:	93gr.