C E N 50130-4

INDOOR SOUNDERS WITH FLASHER







The Smarty is fully microprocessor-controlled and uses piezoelectric sounder and super bright LED-technology flasher. A direct move towards superior signalling features and low power consumption.

The device is tamper protected, and provides a sounder-shutdown input which allows the flasher to continue signalling.


Main features	Smarty/SI	Smarty/GI	
Power	13	13.8 Vdc	
Maximum current draw	1	130 mA	
Sounder- modulation/shutdown input		Yes	
Anti-opening and protection		Yes	
Piezoelectric sounder		Yes	
LED signal flasher	-	Yes	
Light Intensity at 1m	-	25 lux	
Sound pressure at 1m	1:	110 dBA	
Protection Grade		IP31	
Security rating		2	
Environmental class	Ш	II	
Dimensions (HxWxD)	76x1	76x112x30 mm	
Weight		110 g	








Sounderflasher - back




SMARTY



CONNECTION DIAGRAMS



Tamper and volume adjustment connections



ORDER CODES

Smarty/SIB: indoor siren, white color, 12Vdc powered

Smarty/GIB: indoor siren with flasher, white color, 12Vdc powered Smarty/GFR: indoor siren with flasher, red color, 24Vdc powered



Centobuchi, via Dei Lavoratori 10 63076, Monteprandone (AP), ITALY Tel. +39 0735 705007 _ Fax +39 0735 704912